

AS 511 - Specifiche tecniche



Description

AS 511 è particolarmente idoneo per attrezzi agricoli nelle applicazioni con manti erbosi. La carcassa robusta e la miscela del battistrada particolarmente resistente ai tagli garantiscono straordinaria stabilità e performance avanzate. Grazie alla larga area di contatto, AS 511 offre eccellente trazione e minimizza la compattazione del suolo.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 R 15

Dimensions US Standard

Usa code	94059782
Section Width (inch)	15.3
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	13.9
Rolling Circumference (inch)	94
Rim Rec	13 LB
ECE	E11-106R-005098

Load capacity (lbs)

mph / psi	41
30	3305

Printed on 23/04/2024 16:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..