

## AT 108 - Specifiche tecniche



### Description

AT 108 è uno pneumatico per ogni tipo di terreno per i veicoli ATV. Il disegno del battistrada assicura comfort e performance eccellenti su strada e fuori strada.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 20 X 10 - 10

## Dimensions US Standard

Usa code	94052608
Ply Rating	8
Section Width (inch)	9.8
Overall Diameter (inch)	20.2
Static Loaded Radius (inch)	9.3
Rolling Circumference (inch)	60.1
Rim Rec	8.0 AT
Rim Alt	7.5 AT ; 8.5 AT

## Load capacity (lbs)

mph / psi	8
50	340

Printed on 06/05/2024 15:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..