

## AT 110 - Specifiche tecniche



### Description

AT 110 è lo pneumatico BKT adatto per applicazioni 4x4 con veicoli ATV. Grazie al suo straordinario controllo di sterzata, AT 110 è lo pneumatico ideale per l'asse anteriore del tuo veicolo.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 23 X 7 - 10

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	178
Overall Diameter (mm)	584
Rim Rec	5.5 AT
Rim Alt	6.0 AT
ECE	E4-75R-0006334

## Load capacity (Kg)

km/h / bar	0.35
100	109

Printed on 04/05/2024 04:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..