

AT 111 HD - Specifiche tecniche



Description

AT 111 HD è idoneo per competizioni sportive All Terrain con veicoli ATV. La profondità incrementata e il forte spessore dei fianchi offrono estrema aderenza e controllo di frenatura abbinati ad eccellente trazione e controllo ad alta velocità nelle manovre di sovrasterzo. AT 111 HD assicura un ciclo di vita esteso dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 20 X 11 - 10

Dimensions US Standard

Usa code	94027002
Ply Rating	6
Section Width (inch)	11
Overall Diameter (inch)	19.9
Rim Rec	9.0 AT
Rim Alt	8.5 AT
ECE	E4-75R-0006327

Load capacity (lbs)

mph / psi	7
62	330

Printed on 27/04/2024 08:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..