

AT 171 - Specifiche tecniche



Description

AT 171 è stato specificamente progettato per trattori per corse 4x4 nel fango. Il particolare disegno direzionale ed extra profondo del battistrada assicura eccellente trazione su superfici bagnate e fangose.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo ATV • Veicolo per corse nel fango

Version	STANDARD
Type	TL
Tyre Size	AT 33 X 9 - 20
LI/SS	85 A8 / 61 F

Dimensions International Standard

Ply Rating	6
Section Width (mm)	205
Overall Diameter (mm)	838
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2616
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	1.40	1.00
40 MUD BOGGING	515	-
80 MUD BOGGING	257	-
40 CASUAL TRANSPORT	-	425
80 CASUAL TRANSPORT	-	218

Printed on 27/04/2024 23:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..