

AT 171 - Scheda tecnica

Description

AT 171 è stato specificamente progettato per trattori per corse 4x4 nel fango. Il particolare disegno direzionale ed extra profondo del battistrada assicura eccellente trazione su superfici bagnate e fangose.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo ATV • Veicolo per corse nel fango



SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
AT 28 X 9 - 14	STANDARD	R1W+	77 A8 / 53 F	6	W7	W 6	205	715	0	0	TL
AT 30 X 9 - 14	STANDARD	R1W+	77 A8 / 53 F	6	W7	W 6	211	755	0	0	TL
AT 31 X 9 - 16	STANDARD	R1W+	80 A8 / 56 F	6	W7	W 6	211	785	0	0	TL
AT 33 X 8 - 18	STANDARD	R1W+	83 A8 / 59 F	6	W 6	W 5.5	200	845	390	2525	TL
AT 35 X 10 - 18	STANDARD	R1W+	90 A8 / 66 F	8	W 8		241	900	417	2646	TT
AT 35 X 10 - 18	STANDARD	R1W+	90 A8 / 66 F	8	W 8		241	900	417	2646	TL
AT 33 X 9 - 20	STANDARD	R1W+	85 A8 / 61 F	6	W 7	W 6	205	838	387	2616	TL
AT 35 X 9 - 20	STANDARD	R1W+	85 A8 / 61 F	6	W 7	W 6	200	895	419	2670	TL
AT 35 X 9 - 20	STANDARD	R1W+	85 A8 / 61 F	6	W 7	W 6	200	895	419	2670	TT
AT 38 X 10 - 20	STANDARD	R1W+	93 A8 / 69 F	6	W 8	W 7	235	950	442	2835	TT
AT 38 X 10 - 20	STANDARD	R1W+	93 A8 / 69 F	6	W 8	W 7	235	950	442	2835	TL
AT 35 X 9 - 22	STANDARD	R1W+	88 A8 / 64 F	6	W7	W6	210	890	0	0	TL
AT 37 X 9 - 22	STANDARD	R1W+	88 A8 / 64 F	8	W7	W6	205	945	444	2778	TT
AT 37 X 9 - 22	STANDARD	R1W+	88 A8 / 64 F	8	W7	W6	205	945	444	2778	TL
AT 40 X 10 - 22	STANDARD	R1W+	95 A8 / 71 F	8	W 8	W 7	235	1005	469	2955	TT
AT 40 X 10 - 22	STANDARD	R1W+	95 A8 / 71 F	8	W 8	W 7	235	1005	469	2955	TL
AT 40 X 9 - 24	STANDARD	R1W+	90 A8 / 66 F	8	W 7	W 6	211	995	462	3112	TL

Printed on 27/04/2024 19:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..