

AT 603 - Specifiche tecniche



Description

AT 603 è uno pneumatico agro-industriale per attrezzi agricoli e terne. AT 603 è stato progettato per assicurare eccellente durabilità e trazione sulla ruota motrice e quindi ottime performance su ogni superficie, nonché eccellenti proprietà di autopulitura. AT 603 è disponibile in versione "special" con una carcassa rinforzata, mentre la versione "HD" offre una migliore resistenza a tagli e lacerazioni.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Terna • Attrezzi agricoli
Industriale: Terna

Version	SPECIAL
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

Dimensions US Standard

Usa code	94033904
Ply Rating	12
Section Width (inch)	12.1
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	119.2
Rim Rec	W 9
Rim Alt	11
ECE	E4-106R-004350

Load capacity (lbs)

mph / psi	54
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840
5 DW	5710
15 DW	4850
20 DW	4560
25 DW	4080

Printed on 26/04/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..