

## AT 603 - Specifiche tecniche



### Description

AT 603 è uno pneumatico agro-industriale per attrezzi agricoli e terne. AT 603 è stato progettato per assicurare eccellente durabilità e trazione sulla ruota motrice e quindi ottime performance su ogni superficie, nonché eccellenti proprietà di autopulitura. AT 603 è disponibile in versione "special" con una carcassa rinforzata, mentre la versione "HD" offre una migliore resistenza a tagli e lacerazioni.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Terna • Attrezzi agricoli  
Industriale: Terna

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	308
Overall Diameter (mm)	1000
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	3027
SRI (mm)	475
Rim Rec	W 9
Rim Alt	11
ECE	E11-106R-004351

## Load capacity (Kg)

	km/h / bar	4.90
	10 FR	4410
	25 FR	3750
	30 FR	3530
	40 FR	3150
	10 DW	3050
	25 DW	2595
	30 DW	2440
	40 DW	2180

Printed on 26/04/2024 22:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..