

## AW 708 IND - Specifiche tecniche



### Description

AW 708 IND è stato sviluppato per rimorchi industriali. È disponibile una versione "HD" con mescola particolarmente resistente a tagli e strappi.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Rimorchio

Version	INDUSTRIAL
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	149 A8

## Dimensions International Standard

Ply Rating	18
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00
ECE	E11-106R-004254

## Load capacity (Kg)

	km/h / bar	4.50
	10 FR	4550
	25 FR	3870
	30 FR	3640
	40 FR	3250

Printed on 27/04/2024 12:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..