

## AW 708 IND - Specifiche tecniche



### Description

AW 708 IND è stato sviluppato per rimorchi industriali. È disponibile una versione "HD" con mescola particolarmente resistente a tagli e strappi.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Rimorchio

Version	INDUSTRIAL
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	149 A8

## Dimensions US Standard

Usa code	94054213
Ply Rating	18
Section Width (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00
ECE	E11-106R-004254

## Load capacity (lbs)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Printed on 27/04/2024 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..