

## AW 708 - Specifiche tecniche



### Description

AW 708 è stato sviluppato per la lavorazione della terra nonché applicazioni di trasporto e raccolta del fieno con attrezzi agricoli, rimorchi e macchine per la raccolta del fieno/pressapaglia. È disponibile una versione "HD" con miscela speciale resistente a tagli e lacerazioni.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli •  
Rimorchio  
Industriale: Rimorchio

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS FREE ROLLING	140 A8

## Dimensions International Standard

<b>Ply Rating</b>	10
<b>Section Width (mm)</b>	500
<b>Overall Diameter (mm)</b>	945
<b>Static Loaded Radius (mm)</b>	416
<b>Rolling Circumference (mm)</b>	2750
<b>Rim Rec</b>	16.00
<b>ECE</b>	E4-106R-001884

## Load capacity (Kg)

	km/h / bar	2.00
	10 FR	3500
	25 FR	2975
	30 FR	2800
	40 FR	2500

Printed on 26/04/2024 00:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..