

AW 711 - Specifiche tecniche



Description

AW 711 è uno pneumatico radiale per attrezzature agricole, specificamente progettato per l'impiego nell'agricoltura moderna, e adatto per la lavorazione della terra. Grazie alla speciale miscela del battistrada, AW 711 assicura un lungo ciclo di vita del prodotto, sia se utilizzato su superfici morbide che su superfici dure. La bassa resistenza al rotolamento durante il trasferimento su strada garantisce risparmi significativi nel consumo di carburante. Grazie alla tecnologia VF, AW 711 è in grado di portare carichi pesanti a basse pressioni.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Mietitrebbia • Attrezzi agricoli

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 340/65 R 18
LI/SS	153 A8/B

Dimensions US Standard

Usa code	94053476
Section Width (inch)	13
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	106.4
Rim Rec	W 11
ECE	E11-106R-002992

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
From 5 to 30 mph	2580	3380	4110	4750	5480	6210	6680	7330	8050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15/10/2024 00:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..