

BK 308 - Scheda tecnica



Description

BK 308 è stato particolarmente sviluppato per rimorchi e trattori compatti. Lo pneumatico si distingue per l'eccellente trazione su tutte le superfici e elementi intermedi (tie bar) tra i tasselli del battistrada per ridurre l'effetto di crepe di sforzo nel battistrada. La carcassa robusta realizzata con una miscela speciale del battistrada offre eccellente durabilità e ottima resistenza contro la foratura per assicurare una vita operativa più estesa.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore compatto • Rimorchio

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
6.50 - 20	STANDARD	112 A6	10	5.50 F	4.00 E ; 5.00 F	190	865	TT	E11-106R-003563

Printed on 26/04/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..