

BK 6060 - Specifiche tecniche



Description

BK 6060 è uno pneumatico idoneo sia sul campo che sulla strada sviluppato per rimorchi e terne nelle applicazioni di trasporto e per le operazioni di scavo e carico. Il disegno a blocchi del battistrada garantisce un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Terna • Rimorchio

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	255
Overall Diameter (mm)	925
Static Loaded Radius (mm)	427
Rolling Circumference (mm)	2740
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004362

Load capacity (Kg)

km/h / bar	7.25
30	2300

Printed on 27/04/2024 00:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..