

BK 823 - Specifiche tecniche



Description

BK 823 è uno pneumatico progettato per trattori, attrezzi agricoli e rimorchi nelle applicazioni di lavorazione del terreno e di trasporto sia su campo che su strada. Lo speciale disegno a blocchi del battistrada, lo rende particolarmente idoneo per impieghi pesanti in cui ottime prestazioni di sterzata sono un requisito essenziale. È disponibile anche una versione HD con resistenza a tagli e lacerazioni avanzate.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Trattore • Rimorchio

Version	HD
Type	TT
Tyre Size	9.00 - 16
LI/SS	127 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	245
Overall Diameter (mm)	891
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2583
Rim Rec	6.5
ECE	E11-106R-004338

Load capacity (Kg)

km/h / bar	4.40
40	1750

Printed on 26/04/2024 21:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..