

BK 823 - Scheda tecnica



Description

BK 823 è un pneumatico progettato per trattori, attrezzi agricoli e rimorchi nelle applicazioni di lavorazione del terreno e di trasporto sia su campo che su strada. Lo speciale disegno a blocchi del battistrada, lo rende particolarmente idoneo per impieghi pesanti in cui ottime prestazioni di sterzata sono un requisito essenziale. È disponibile anche una versione HD con resistenza a tagli e lacerazioni avanzate.

UM

International Standard

Construction

✦ BIAS

Machinery

Agricoltura: Attrezzi agricoli • Trattore • Rimorchio

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	127 A8	14	6.5		245	891	394	2583	TT	E11-106R-004338
9.00 - 16	STANDARD	124 A8	12	6.5		245	891	394	2583	TT	E11-106R-003603
9.00 - 16	STANDARD	127 A8	14	6.5		245	891	394	2583	TT	E11-106R-003604
9.00 - 16	STANDARD	121 A8	10	6.5		245	891	394	2583	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/01/2025 21:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..