

BK 826 - Specifiche tecniche



Description

BK 826 è stato specialmente progettato per rimorchi nelle applicazioni di trasporto. È un pneumatico diagonale caratterizzato da elevata capacità di carico grazie alla carcassa rinforzata. BK 826 è disponibile anche come versione "industrial" che offre una particolare resistenza ai tagli ed è anche idoneo per terne.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

Industriale: Terna • Rimorchio

Version	TRACTOR TRAILER
Type	TT
Tyre Size	9.00 - 16
LI/SS	138 A6

Dimensions International Standard

Ply Rating	18
Section Width (mm)	265
Overall Diameter (mm)	925
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-005356

Load capacity (Kg)

km/h / bar	7.60
30	2360

Printed on 14/04/2024 06:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..