

## BK RUF N TUF - Specifiche tecniche



### Description

BK RUF N TUF è uno pneumatico con disegno a blocchi del battistrada, idoneo per operazioni di trasporto con rimorchi e camioncini. È ideale per l'impiego su strada e garantisce un'ottima durevolezza.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Autocarro leggero • Rimorchio

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	216
<b>Overall Diameter (mm)</b>	830
<b>Rim Rec</b>	6.00 G
<b>Rim Alt</b>	5.50 F

## Load capacity (Kg)

	km/h / bar	<b>6.90</b>
	<b>100 LS</b>	1500
	<b>100 LD</b>	1320

Printed on 06/05/2024 22:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..