

## BOGMAX - Specifiche tecniche



### Description

BOGMAX è stato particolarmente sviluppato per applicazioni ATV. Il disegno molto profondo del battistrada garantisce eccellente trazione, mentre i cordoli di protezione del fianco riducono gli impatti e il rischio di possibili danni. BOGMAX è uno pneumatico a 6 tele con tecnologia M + S - perfetto per prestazioni sportive in ogni condizione.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 30 X 10 - 14
LI/SS	58 F

## Dimensions US Standard

Usa code	94052851
Ply Rating	6
Section Width (inch)	10.2
Overall Diameter (inch)	29.9
Rim Rec	7.0 AT
Rim Alt	7.5 AT ; 8.0 AT

## Load capacity (lbs)

mph / psi	7
50	520

Printed on 25/04/2024 22:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..