

COMMANDER (R) - Specifiche tecniche



Description

COMMANDER (R) è uno pneumatico agricoltura caratterizzato da un battistrada profondo con una base forte dei tasselli che assicurano un ciclo di vita prolungato dello pneumatico. Lo speciale disegno dei tasselli a due angolazioni garantisce sia un'eccellente trazione sul campo che ottime qualità di autopulitura. La robusta carcassa è realizzata con una miscela particolarmente resistente ad ogni tipo di taglio che fornisce una migliore resistenza alla perforazione nonché elevata capacità di carico. COMMANDER (R) è lo pneumatico perfetto per la lavorazione del terreno nonché le operazioni di trasporto e di raccolto.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Mietitrebbia • Trattore

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 16.9 - 28 |
| LI/SS | 139 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94048212 |
| Ply Rating | 12 |
| TMPH | 1 |
| Section Width (inch) | 17.3 |
| Overall Diameter (inch) | 56.5 |
| Static Loaded Radius (inch) | 26.1 |
| Rolling Circumference (inch) | 168.3 |
| Rim Rec | W 15 L |
| Rim Alt | W 14 L |
| ECE | E11-106R-003627 |
| TRA Code | R1 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 35 |
| 25 | 5355 |

Printed on 25/04/2024 19:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..