

CONTAINER KING - Specifiche tecniche



Description

CONTAINER KING è stato particolarmente sviluppato per i reach stacker nelle applicazioni intermodali di trasporto e nella logistica. Questo straordinario pneumatico è stato realizzato con una miscela del battistrada estremamente resistente all'usura, riducendo le crepe sul battistrada. CONTAINER KING assicura un ciclo di vita prolungato oltre ad eccezionale stabilità in modalità di sollevamento.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Reach Stacker

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94069798
Ply Rating	24
Overall Width (inch)	13
Overall Diameter (inch)	50.6
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	22650

Printed on 28/04/2024 22:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..