

## CRANE SPECIAL - Specifiche tecniche

### Description

CRANE SPECIAL è idoneo per gru mobili "pick & carry" su terreni impervi. Lo pneumatico è realizzato con una speciale miscela che fornisce elevata stabilità e durabilità.



### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Gru mobile

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94041213
Ply Rating	32
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3

Load capacity (lbs)

mph / psi	83
30	19300

Printed on 07/05/2024 15:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..