

## DESERT KING - Specifiche tecniche



### Description

DESERT KING è ideale per terreni morbidi, terreni sabbiosi e applicazioni di pavimentazione con truck da deserto. Il design ottimizzato del battistrada con nervatura offre un galleggiamento e una stabilità direzionale eccellenti. La robusta carcassa in nylon e il tallone per impieghi gravosi sono sviluppati in modo specifico per operazioni a bassa pressione. DESERT KING presenta anche un'elevata resistenza alle forature e una maggiore durata.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Truck da deserto

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25 DT

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	470
Overall Diameter (mm)	1535
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4405
Rim Rec	10.00/1.5
TRA Code	E7

## Load capacity (Kg)

	km/h / bar	2.50
	10	7500
	50	5150
	65	4375

Printed on 26/04/2024 22:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..