

DESERT KING - Scheda tecnica



Description

DESERT KING è ideale per terreni morbidi, terreni sabbiosi e applicazioni di pavimentazione con truck da deserto. Il design ottimizzato del battistrada con nervatura offre un galleggiamento e una stabilità direzionale eccellenti. La robusta carcassa in nylon e il tallone per impieghi gravosi sono sviluppati in modo specifico per operazioni a bassa pressione. DESERT KING presenta anche un'elevata resistenza alle forature e una maggiore durata.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Truck da deserto

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
18.00 - 25 DT	STANDARD	E7	16	10.00/1.5		470	1535	635	4405	TL
21.00 - 25 DT	STANDARD	E7	16	15.00/3.0		570	1660	708	4906	TL
29.5 - 25 DT	STANDARD	E7	28	25.00/3.5		770	1822	786	5392	TL

Printed on 26/04/2024 20:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..