

EARTHMAX SR 25 PLUS - Specifiche tecniche



Description

EARTHMAX SR 25 PLUS (G-2/L-2) è uno pneumatico radiale All Steel particolarmente progettato per motolivellatrici e loader che operano nelle applicazioni più dure nelle applicazioni di costruzione stradale e minerarie. Il disegno non direzionale del battistrada offre eccellenti proprietà di auto-pulitura insieme a ottime trazione e stabilità fuori strada.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Dozer • Motolivellatrice • Pala caricatrice
OTR: Dozer • Motolivellatrice • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	153 A8/175 A2

Dimensions US Standard

Usa code	94044962
Overall Width (inch)	14.1
Overall Diameter (inch)	54
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	163.2
Rim Rec	8.00TG
Rim Alt	9.00GR
Star Rating	*
TRA Code	G2/L2
Tread Depth	32

Load capacity (lbs)

mph / psi	29	33	36	40	44	47	51	54	76	80
25	4940	5360	5840	6150	6600	7150	7400	8050	-	-
5	-	-	-	-	-	-	-	-	14800	15200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 20/05/2025 14:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..