

EARTHMAX SR 30 - Specifiche tecniche



Description

EARTHMAX SR 30 (E-3/L-3) è uno pneumatico radiale *All Steel* progettato per il duplice impiego con loader o dumper articolati. Le cinture d'acciaio multistrato e il disegno rigido a blocchi assicurano trazione, stabilità e durabilità eccellenti. La speciale mescola resistente al taglio rende EARTHMAX SR 30 la soluzione ideale per una varietà di condizioni operative dure.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Dumper articolato, Dozer, Pala caricatrice

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 26.5 R 25 |
| LI/SS | 193 B |

Dimensions International Standard

| | |
|----------------------------|--------------|
| TKPH | 230 |
| Overall Width (mm) | 689 |
| Overall Diameter (mm) | 1742 |
| Static Loaded Radius (mm) | 766 |
| Rolling Circumference (mm) | 5200 |
| Rim Rec | 22.00/3.0 |
| Rim Alt | 22.00/3.0 IF |
| Star Rating | ** |
| TRA Code | E3 |

Load capacity (Kg)

| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|------|------|-------|-------|-------|-------|
| 50 | 9500 | 9750 | 10300 | 10600 | 11200 | 11500 |

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..