

## EARTHMAX SR 313 - Scheda tecnica



### Description

EARTHMAX SR 313 è uno pneumatico radiale All Steel specificamente progettato per dumper articolati e pale che operano in condizioni rocciose difficili. La sua mescola resistente al taglio e lo speciale design del battistrada proteggono da tagli e danni, insieme alle proprietà autopulenti. Il design quadrato della spalla massimizza il contatto con il suolo per un'eccellente manovrabilità. La costruzione radiale All Steel con cinghie in acciaio multistrato garantisce una maggiore durata. EARTHMAX SR 313 è lo pneumatico ideale per operazioni di carico e trasporto.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper articolato • Pala caricatrice

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
15.5 R 25	CUT RESISTANT COMPOUND	94066964	E3/L3	**/*	160 B/169 A2	12.00/1.3		15.5	49.8	22.3	150.5	TL	92

Printed on 21/04/2024 23:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..