

EARTHMAX SR 32 - Specifiche tecniche



Description

EARTHMAX SR 32 è uno pneumatico radiale di base larga non direzionale particolarmente idoneo per scraper (ruspe). Lo pneumatico è caratterizzato da una carcassa All Steel robusta e da una miscela speciale che assicurano elevata resistenza a tagli e perforazioni nonché durabilità. Ulteriori vantaggi sono trazione e galleggiamento eccellenti anche durante operazioni di servizio pesante.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Ruspa

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	37.25 R 35
LI/SS	218 B

Dimensions International Standard

TKPH	453
Overall Width (mm)	963
Overall Diameter (mm)	2381
Static Loaded Radius (mm)	1062
Rolling Circumference (mm)	7229
Rim Rec	31.00/4.0
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	19500	20600	21200	22400	23000	23600

Printed on 12/05/2024 01:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..