

EARTHMAX SR 33 PLUS - Scheda tecnica



Description

Earthmax SR 33 PLUS è uno pneumatico radiale con un disegno a blocchi multipli che è stato progettato per garantire eccellente galleggiamento su superfici morbide, sabbiose e fangose. La carcassa All Steel si distingue per l'eccellente durabilità e la resistenza contro tagli e perforazioni. Earthmax SR 33 offre proprietà di autopulitura straordinarie nonché stabilità superiore.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Veicolo universale

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
16.00 R 20	STANDARD	173/170 G	11.25	10.00W, 10.0	448	1310	582	3974	TL	E11-54R-0017916

Printed on 23/04/2024 13:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..