

EARTHMAX SR 33 - Scheda tecnica



Description

Earthmax SR 33 è uno pneumatico radiale per veicoli universali. Il particolare disegno a blocchi è stato progettato per garantire eccellente trazione su superfici morbide, sabbiose o fangose. Earthmax SR 33 offre ottima stabilità oltre a proprietà di autopulitura straordinarie. La carcassa All Steel si distingue per l'eccellente durabilità e la resistenza contro tagli e forature.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Veicolo universale

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
14.00 R 20	STANDARD	94057757	164/160 J	10.0	9.0, 10.00W	15.4	49.2	22.7	151.2	TL	E11-54R-0016678
335/80 R 20	STANDARD	94059478	150 K	11		13.2	41.2	18.3	123.8	TL	E11-54R-0016679
365/80 R 20 (14.5 R 20)	STANDARD	94061907	152 K	11		14.2	43.1	19.5	130.6	TL	E11-54R-0017314
395/85 R 20	STANDARD	94050611	168 J	10.00W	10.00HF	15.5	46.6	21.2	141.3	TL	E11-54R-0017315

Printed on 24/04/2024 05:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..