

EARTHMAX SR 412 - Specifiche tecniche



Description

EARTHMAX SR 412 (E-4/L-4) è uno pneumatico radiale All Steel particolarmente progettato per dumper articolati, loader e dozer. Il disegno unico del battistrada con profondità E-4 assicura eccellente trazione e straordinaria resistenza al calore. Grazie alla robusta carcassa e le cinture All Steel, EARTHMAX SR 412 è in grado di trasportare carichi pesanti, garantendo eccezionale stabilità nonché resistenza a lacerazioni e forature. La spalla di forma quadrata di EARTHMAX SR 412 offre massimo contatto con il terreno e quindi eccellente manovrabilità.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	750/65 R 25 (30/65 R 25)
LI/SS	190 B/202 A2

Dimensions International Standard

TKPH	229
Overall Width (mm)	780
Overall Diameter (mm)	1602
Static Loaded Radius (mm)	715
Rolling Circumference (mm)	4838
Rim Rec	24.00/3.0
Rim Alt	22.00/3.0, 25.00/3.0
Star Rating	**/*
TRA Code	E4/L4

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
50	9500	9750	10300	10600
10	13200	14000	14500	15000

Printed on 20/04/2024 04:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..