

EARTHMAX SR 412 - Scheda tecnica



Description

EARTHMAX SR 412 (E-4/L-4) è uno pneumatico radiale All Steel particolarmente progettato per dumper articolati, loader e dozer. Il disegno unico del battistrada con profondità E-4 assicura eccellente trazione e straordinaria resistenza al calore. Grazie alla robusta carcassa e le cinture All Steel, EARTHMAX SR 412 è in grado di trasportare carichi pesanti, garantendo eccezionale stabilità nonché resistenza a lacerazioni e forature. La spalla di forma quadrata di EARTHMAX SR 412 offre massimo contatto con il terreno e quindi eccellente manovrabilità.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
29.5 R 25	CUT RESISTANT COMPOUND	E4	**	200 B	25.00/3.5		765	1865	834	5543	TL	252
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E4/L4	**/*	190 B/202 A2	24.00/3.0	22.00/3.0; 25.00/3.0	780	1602	715	4838	TL	229
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E4	**	190 B	24.00/3.0	22.00/3.0; 25.00/3.0	780	1602	715	4838	TL	229
800/65 R 29	CUT RESISTANT COMPOUND	E4/L4	**/*	198 B / 208 A2	27.00/3.0	24.00/3.5 , 25.00/3.5	790	1805	825	5490	TL	206

Printed on 20/04/2024 13:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..