

## EARTHMAX SR 41 - Specifiche tecniche



### Description

EARTHMAX SR 41 è uno pneumatico radiale All Steel ideale per loader and dozer nelle applicazioni di trasporto, carico e livellamento. Grazie alla sua struttura in acciaio e al particolare disegno a blocchi, EARTHMAX SR 41 offre un'eccellente resistenza alle forature e una durabilità prolungata. Oltre a molte ore operative senza tempi di fermo macchina, lo pneumatico assicura un comfort eccezionale. EARTHMAX SR 41 (E-4/L-4) è uno pneumatico All Steel ideale per dumper articolati, loader e dozer.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice • Dumper di basso profilo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/195 A2

## Dimensions US Standard

Usa code	94053353
TMPH	110
Overall Width (inch)	24.2
Overall Diameter (inch)	63.4
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	188.6
Rim Rec	19.50/2.5
Star Rating	**/*
TRA Code	E4/L4

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	16500	17100	18200	18700	19800	20400
5	22700	23400	24700	25400	26800	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/12/2024 19:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..