EARTHMAX SR 423 - Specifiche tecniche

Description

EARTHMAX SR 423 è uno pneumatico radiale All Steel idoneo per una serie di applicazioni, incluse le operazioni nelle cave, di trasporto e forestiere. Il disegno non direzionale del battistrada assicura trazione e stabilità eccellenti su qualsiasi tipo di terreno. Lo pneumatico è ideale per il trasporto di carichi pesanti. La carcassa robusta All Steel si distingue per la straordinaria resistenza all'usura nonché l'ottima resistenza contro tagli e forature. Il battistrada rinforzato e il disegno della spalla contribuiscono ad un ciclo di vita prolungato anche in condizioni di servizio pesante.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Carro con cassone ribaltabile

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	149/146 J

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	270
Overall Diameter (mm)	1065
Rim Rec	7.50
Rim Alt	8.00

Load capacity (Kg)

km/h / bar	8.30
100 Load Single	3250
100 Load Dual	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 11:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..