

EARTHMAX SR 431 - Specifiche tecniche



Description

EARTHMAX SR 431 (E-4) è uno pneumatico radiale All Steel particolarmente progettato per dumper rigidi che operano in condizioni severe nelle miniere a cielo aperto e sotterranee. Il disegno non direzionale del battistrada assicura trazione e stabilità eccellenti. Lo pneumatico è caratterizzato da una carcassa All Steel robusta e da una miscela speciale che garantiscono elevata resistenza a tagli e perforazioni nonché un ciclo di vita più lungo anche in ambienti rocciosi, abrasivi ed ostili.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 25
LI/SS	185 B

Dimensions International Standard

TKPH	140
Overall Width (mm)	520
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	760
Rolling Circumference (mm)	5040
Rim Rec	13.00/2.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	7300	7500	7750	8000	8250	8500	8750	9000	9250

Printed on 22/02/2024 23:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..