

## EARTHMAX SR 431 - Scheda tecnica



### Description

EARTHMAX SR 431 (E-4) è uno pneumatico radiale All Steel particolarmente progettato per dumper rigidi che operano in condizioni severe nelle miniere a cielo aperto e sotterranee. Il disegno non direzionale del battistrada assicura trazione e stabilità eccellenti. Lo pneumatico è caratterizzato da una carcassa All Steel robusta e da una miscela speciale che garantiscono elevata resistenza a tagli e perforazioni nonché un ciclo di vita più lungo anche in ambienti rocciosi, abrasivi ed ostili.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
16.00 R 25	CUT RESISTANT COMPOUND	E4	**	177 B	11.25/2.0		452	1532	713	4649	TL	166
18.00 R 25	CUT RESISTANT COMPOUND	E4	**	185 B	13.00/2.5		520	1660	760	5040	TL	140
18.00 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		13.00/2.5		520	1660	760	5040	TL	

Printed on 22/02/2024 20:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..