

## EARTHMAX SR 45 H2 - Scheda tecnica



### Description

EARTHMAX SR 45 H2 è uno pneumatico radiale **All Steel** particolarmente progettato per dumper rigidi. Il disegno unico del battistrada con profondità E-4 riduce l'usura e minimizza vibrazioni e rumori. EARTHMAX SR 45 H2 è ideale per tutte le operazioni che richiedono trazione e stabilità. Grazie alla struttura All Steel, lo pneumatico assicura eccellente resistenza a lacerazioni e forature nonché un ciclo di vita più lungo. Disponibile con miscela standard, resistente ai tagli o resistente al calore.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	333
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	333
24.00 R 35	HEAT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	435
24.00 R 35	HEAT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5		660	2180	978	6597	TL	435
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	390
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	390

Printed on 09/05/2024 10:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..