

## EARTHMAX SR 45 H2 - Scheda tecnica



### Description

EARTHMAX SR 45 H2 è uno pneumatico radiale **All Steel** particolarmente progettato per dumper rigidi. Il disegno unico del battistrada con profondità E-4 riduce l'usura e minimizza vibrazioni e rumori. EARTHMAX SR 45 H2 è ideale per tutte le operazioni che richiedono trazione e stabilità. Grazie alla struttura All Steel, lo pneumatico assicura eccellente resistenza a lacerazioni e forature nonché un ciclo di vita più lungo. Disponibile con mescola standard, resistente ai tagli o resistente al calore.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

| SIZE       | Version                 | USACode  | TRA Code | Star R | LI/SS | RIM REC   | RIM ALT | OW | OD   | SLR  | RC    | Type | TMPH |
|------------|-------------------------|----------|----------|--------|-------|-----------|---------|----|------|------|-------|------|------|
| 24.00 R 35 | CUT RESISTANT COMPOUND  | 94060221 | E4       | **     | 209 B | 17.00/3.5 | --      | 26 | 85.8 | 38.5 | 259.7 | TL   | 228  |
| 24.00 R 35 | CUT RESISTANT COMPOUND  | 94063802 | E4       | ***    | 212 B | 17.00/3.5 | ---     | 26 | 85.8 | 38.5 | 259.7 | TL   | 228  |
| 24.00 R 35 | HEAT RESISTANT COMPOUND | 94060764 | E4       | **     | 209 B | 17.00/3.5 |         | 26 | 85.8 | 38.5 | 259.7 | TL   | 298  |
| 24.00 R 35 | HEAT RESISTANT COMPOUND | 94063826 | E4       | ***    | 212 B | 17.00/3.5 | ---     | 26 | 85.8 | 38.5 | 259.7 | TL   | 298  |
| 24.00 R 35 | STANDARD COMPOUND       | 94059720 | E4       | **     | 209 B | 17.00/3.5 | --      | 26 | 85.8 | 38.5 | 259.7 | TL   | 267  |
| 24.00 R 35 | STANDARD COMPOUND       | 94063819 | E4       | ***    | 212 B | 17.00/3.5 | ---     | 26 | 85.8 | 38.5 | 259.7 | TL   | 267  |

Printed on 30/05/2023 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..