

EARTHMAX SR 45 PLUS - Specifiche tecniche



Description

EARTHMAX SR 45 PLUS è uno pneumatico radiale All Steel specialmente progettato per dumper rigidi ed è ideale per operazioni su percorsi lunghi. Il disegno del battistrada di EARTHMAX SR 45 PLUS minimizza vibrazioni e rumori.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Dumper rigido

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 33.00 R 51 |
| LI/SS | 235 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94073306 |
| TMPH | 414 |
| Overall Width (inch) | 35.8 |
| Overall Diameter (inch) | 120.7 |
| Static Loaded Radius (inch) | 53.9 |
| Rolling Circumference (inch) | 366.7 |
| Rim Rec | 24.00/5.0 |
| Star Rating | ** |
| TRA Code | E4 |
| Tread Depth | 113 |

Load capacity (lbs)

| | | | | | | | | | |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
| 30 | 66000 | 68000 | 71500 | 74000 | 76000 | 78500 | 80500 | 82500 | 85500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/05/2025 19:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..