

EARTHMAX SR 45 PLUS - Scheda tecnica

Description

EARTHMAX SR 45 PLUS è uno pneumatico radiale All Steel specialmente progettato per dumper rigidi ed è ideale per operazioni su percorsi lunghi. Il disegno del battistrada di EARTHMAX SR 45 PLUS minimizza vibrazioni e rumori.



UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
27.00 R 49	CUT RESISTANT COMPOUND	94045655	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	301
27.00 R 49	HEAT RESISTANT COMPOUND	94049813	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	448
27.00 R 49	STANDARD COMPOUND	94049806	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	370
33.00 R 51	CUT RESISTANT COMPOUND	94073306	E4	**	235 B	24.00/5.0		35.8	120.7	53.9	366.7	TL	414
33.00 R 51	HEAT RESISTANT COMPOUND	94073320	E4	**	235 B	24.00/5.0		35.8	120.7	53.9	366.7	TL	558
33.00 R 51	STANDARD COMPOUND	94073313	E4	**	235 B	24.00/5.0		35.8	120.7	53.9	366.7	TL	483

Printed on 08/05/2024 22:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..