

EARTHMAX SR 452 - Scheda tecnica



Description

EARTHMAX SR 452 è uno pneumatico radiale All Steel particolarmente progettato per dumper articolati nelle operazioni di trasporto. Il disegno unico del battistrada con profondità E-4 assicura eccellente trazione e straordinaria resistenza al calore. Inoltre, minimizza vibrazioni e rumori offrendo la migliore manovrabilità e ottimo comfort. La robusta carcassa e le cinture in acciaio garantiscono eccellente stabilità nonché resistenza a tagli e forature. La spalla di forma quadrata di EARTHMAX SR 452 offre massimo contatto con il terreno e quindi eccellente manovrabilità.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94063383	E4	**	209 B	17.00/3.5		26	85.4	39.2	264.9	TL	243
24.00 R 35	CUT RESISTANT COMPOUND	94063970	E4	***	212 B	17.00/3.5		26	85.4	39.2	264.9	TL	243
24.00 R 35	STANDARD COMPOUND	94063833	E4	**	209 B	17.00/3.5		26	85.4	39.2	264.9	TL	284
24.00 R 35	STANDARD COMPOUND	94063987	E4	***	212 B	17.00/3.5		26	85.4	39.2	264.9	TL	284

Printed on 22/02/2024 20:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..