

## EARTHMAX SR 454 - Specifiche tecniche



### Description

EARTHMAX SR 454 è uno pneumatico radiale All Steel specificamente progettato per camion rigidi da trasporto. L'esclusivo design del battistrada E-3 e la speciale scanalatura centrale forniscono trazioni laterali ottimizzate e una migliore maneggevolezza sia su superfici morbide che fangose. Questo pneumatico è stato appositamente progettato per consentire velocità più elevate e lunghi viaggi a temperature di esercizio più basse. La costruzione All Steel con cinghie in acciaio multistrato offre una protezione superiore contro urti e penetrazione di frammenti di rocce, per migliorare i tempi di attività con la conseguenza di una maggiore produttività. La spalla quadrata di EARTHMAX SR 454 massimizza il contatto con il suolo per una manovrabilità e una stabilità eccellenti, oltre a vibrazioni e rumore ridotti al minimo.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	40.00 R 57
LI/SS	250 B

## Dimensions US Standard

Usa code	94075553
TMPH	823
Overall Width (inch)	43.9
Overall Diameter (inch)	138.2
Static Loaded Radius (inch)	62.3
Rolling Circumference (inch)	419.4
Rim Rec	29.00/6.0
Rim Alt	32.00/6.0
Star Rating	**
TRA Code	E3

## Load capacity (lbs)

mph / psi	80	83	87	91	94	98	102
30	110000	113500	117000	120000	123500	128000	132500

Printed on 17/04/2024 04:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..