

## EARTHMAX SR 454 - Scheda tecnica



### Description

EARTHMAX SR 454 è uno pneumatico radiale All Steel specificamente progettato per camion rigidi da trasporto. L'esclusivo design del battistrada E-3 e la speciale scanalatura centrale forniscono trazioni laterali ottimizzate e una migliore maneggevolezza sia su superfici morbide che fangose. Questo pneumatico è stato appositamente progettato per consentire velocità più elevate e lunghi viaggi a temperature di esercizio più basse. La costruzione All Steel con cinghie in acciaio multistrato offre una protezione superiore contro urti e penetrazione di frammenti di rocce, per migliorare i tempi di attività con la conseguenza di una maggiore produttività. La spalla quadrata di EARTHMAX SR 454 massimizza il contatto con il suolo per una manovrabilità e una stabilità eccellenti, oltre a vibrazioni e rumore ridotti al minimo.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	525
27.00 R 49	HEAT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	725
27.00 R 49	STANDARD COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	640
33.00 R 51	CUT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	884
33.00 R 51	HEAT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1215
33.00 R 51	STANDARD COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1023
40.00 R 57	CUT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1201
40.00 R 57	HEAT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1740
40.00 R 57	STANDARD COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1462

Printed on 17/04/2024 05:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..