

EARTHMAX SR 45 - Scheda tecnica

Description

EARTHMAX SR 45 è uno pneumatico radiale **All Steel** particolarmente progettato per dumper rigidi. EARTHMAX SR 45 è lo pneumatico ideale per tutte le operazioni che richiedono elevata trazione.



UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
18.00 R 33	CUT RESISTANT COMPOUND	94041145	E4	**	191 B	13.00/2.5	--	19.9	73.6	33.7	220.8	TL	127
18.00 R 33	CUT RESISTANT COMPOUND	94053803	E4	***	195 B	13.00/2.5		19.9	73.6	33.7	220.8	TL	127
18.00 R 33	HEAT RESISTANT COMPOUND	94041855	E4	**	191 B	13.00/2.5	--	19.9	73.6	33.7	220.8	TL	175
18.00 R 33	STANDARD COMPOUND	94041138	E4	**	191 B	13.00/2.5	--	19.9	73.6	33.7	220.8	TL	151
18.00 R 33	STANDARD COMPOUND	94064830	E4	***	195 B	13.00/2.5		19.9	73.6	33.7	220.8	TL	151

Printed on 23/04/2024 12:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..