



EARTHMAX SR 47 TP - Specifiche tecniche

Description

EARTHMAX SR 47 TP (E-4) è uno pneumatico radiale All Steel specificamente progettato per dumper rigidi per il trasporto, che operano in condizioni che richiedono la massima trazione e resistenza alla perforazione. La profondità del battistrada E-4 garantisce resistenza all'usura anche su lunghi tragitti, riducendo i tempi di inattività e aumentando la produttività. EARTHMAX SR 47 TP è perfetto per qualsiasi attività che richieda trazione e stabilità, in particolare su terreni fangosi o scivolosi. Disponibile in mescole standard e resistenti al taglio.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions International Standard

TKPH	377
Overall Width (mm)	650
Overall Diameter (mm)	2185
Static Loaded Radius (mm)	985
Rolling Circumference (mm)	6625
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Printed on 06/05/2024 10:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..