



EARTHMAX SR 47 TP - Scheda tecnica

Description

EARTHMAX SR 47 TP (E-4) è uno pneumatico radiale All Steel specificamente progettato per dumper rigidi per il trasporto, che operano in condizioni che richiedono la massima trazione e resistenza alla perforazione. La profondità del battistrada E-4 garantisce resistenza all'usura anche su lunghi tragitti, riducendo i tempi di inattività e aumentando la produttività. EARTHMAX SR 47 TP è perfetto per qualsiasi attività che richieda trazione e stabilità, in particolare su terreni fangosi o scivolosi. Disponibile in mescole standard e resistenti al taglio.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94074204	E4	**	209 B	17.00/3.5	--	25.6	86	38.8	260.8	TL	258
24.00 R 35	STANDARD COMPOUND	94074211	E4	**	209 B	17.00/3.5	--	25.6	86	38.8	260.8	TL	301

Printed on 06/05/2024 06:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..