

EARTHMAX SR 475 - Specifiche tecniche



Description

EARTHMAX SR 475 è uno pneumatico radiale All Steel particolarmente progettato per dumper rigidi. È ideale per operazioni in ambienti duri e rocciosi e per trasporti lunghi. Il disegno unico del battistrada genera meno calore nei climi caldi e assicura trazione eccellente. La sua carcassa All Steel e le cinture garantiscono straordinaria stabilità e resistenza a tagli e perforazioni. EARTHMAX SR 475 è stato sviluppato con una spalla quadrata che assicura eccellente manovrabilità, ottimizzando il contatto sul terreno.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	191 B

Dimensions International Standard

TKPH	265
Overall Width (mm)	490
Overall Diameter (mm)	1860
Static Loaded Radius (mm)	860
Rolling Circumference (mm)	5721
Rim Rec	13.00/2.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	8500	8750	9000	9250	9750	10000	10300	10600	10900

Printed on 06/12/2023 21:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..