

## EARTHMAX SR 475 - Specifiche tecniche



### Description

EARTHMAX SR 475 è uno pneumatico radiale All Steel particolarmente progettato per dumper rigidi. È ideale per operazioni in ambienti duri e rocciosi e per trasporti lunghi. Il disegno unico del battistrada genera meno calore nei climi caldi e assicura trazione eccellente. La sua carcassa All Steel e le cinture garantiscono straordinaria stabilità e resistenza a tagli e perforazioni. EARTHMAX SR 475 è stato sviluppato con una spalla quadrata che assicura eccellente manovrabilità, ottimizzando il contatto sul terreno.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	191 B

## Dimensions US Standard

Usa code	94064397
TMPH	182
Overall Width (inch)	19.3
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	33.9
Rolling Circumference (inch)	225.2
Rim Rec	13.00/2.5
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	18700	19300	19800	20400	21500	22000	22700	23400	24000

Printed on 09/12/2023 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..