

EARTHMAX SR 47 - Specifiche tecniche



Description

EARTHMAX SR 47 (E-4) è uno pneumatico radiale **All Steel** particolarmente progettato per dumper rigidi che operano in condizioni nelle quali è richiesta la massima resistenza contro tagli e perforazioni in ambienti rocciosi. Il disegno unico del battistrada con profondità E-4 riduce l'usura assicurando una vita più lunga allo pneumatico anche sui percorsi lunghi. Ciò si traduce in tempi di fermo macchina ridotti, incrementando la produttività. Disponibile con mescola standard o resistente ai tagli.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions International Standard

TKPH	168
Overall Width (mm)	510
Overall Diameter (mm)	1885
Static Loaded Radius (mm)	867
Rolling Circumference (mm)	5674
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

Printed on 24/04/2024 03:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..