

EARTHMAX SR 48 - Specifiche tecniche



Description

EARTHMAX SR 48 è uno pneumatico All Steel specificamente sviluppato per dumper rigidi. Questo pneumatico assicura maggiore trazione e straordinaria resistenza all'usura anche nelle operazioni più ardue in ambienti rocciosi. È ideale per il trasporto di carichi pesanti. La spalla di forma quadrata protegge il fianco da tagli e danni. EARTHMAX SR 48 mostra una robusta carcassa All Steel che offre eccezionale protezione contro urti e perforazioni di sassi ottimizzando la produttività.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions US Standard

Usa code	94060276
TMPH	212
Overall Width (inch)	26.2
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	39.1
Rolling Circumference (inch)	260.7
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 25/04/2024 17:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..